

# PROTECTIVE FLOORING ECOTECK EVENT



PROTECTS YOUR LAWN • QUICK INSTALLATION AND EASY DISMANTLING

|   |  |
|---|--|
| Size:                                   | without a lock<br>306*102 (mm)   |
| Weight:                                 | weight of product<br>112 ± 4(gr)   |
| Material:                               | polypropylene  |
| Color:                                  | <input type="checkbox"/> transparent<br><input checked="" type="checkbox"/> green<br><input type="checkbox"/> metallic<br><input type="checkbox"/> chocolate |
| UV:                                     | resistance to UV   |
| Connection:                             | built-in mechanism of<br>reliable lock   |
| Load:                                   | max load on a solid<br>surface is 29 ton/ sq. m  |
| Class of fire<br>danger of<br>material: | CM3  |
| Operating<br>temperature:               | -10...+50 °C   |
| Chemical<br>resistance:                 | acids, solvents, petrol<br>resistance  |
| Number of<br>modules<br>(pieces):       | 32 of pieces in 1 sq. m  |
| Guarantee:                              | 3 year   |



**MAX 29 T/M2**

## Modules

**ECOTECK™** The modules in assembled form to turn into roll what important for mounting/dismounting, storage, transport (the turn of modules up to 90 degrees)

## Simplicity - 123

**ECOTECK™** Especially for sensitive surface the inside part of modular is various, the weight is divided into several stiffeners, there are no sharp corners and protuberances what excludes the possibility of damage lawn or other flooring

## Reliable protection

**ECOTECK™** The modules have a special of drainage system to provide watering, ventilation and skips the sun for growth grass. No ingress of debris and dirt.